

# TYPHOON HOT 350-23

**5075**  
**PSI**

**23**  
**L/PM**

**HONDA GX690**  
**PETROL**  
**ENGINE TYPE**  
POWERED BY  
**HONDA**

**GEARBOX**  
**1450RPM**  
**DRIVE**





**HOT**  
**WATER**  
**OUTPUT**



## HERO INNOVATIONS







-  **GENYSIS™**  
12v Advanced Burner Control System
-  **PEXO™**  
Stainless Steel Exoskeleton
-  **JWPP™**  
Jetwave Italian Premium Pump
-  **CC™**  
Centralised Control
-  **AVPS™**  
Anti Vibration Protection System

## APPLICATIONS

-  Plumbers
-  Council & Municipality
-  Hot Water Drain Cleaning
-  Water Authorities



## STANDOUT FEATURES

-  JW® Enhanced Italian triplex plunger pump running at 1450RPM delivers more performance and longer life.
-  Electric start Industrial V-Twin Honda™ GX690 Series Engine with digital engine hour meter.
-  Jetwave Safety System™ (JSS) thermal and safety valve to prevent overheating in excessive bypass and over pressurisation.
-  Vertical burner with GeniSys™ 12v Advanced Burner Control with smart sensors and protective features.
-  Battery isolator.
-  Emergency stop.

## STANDARD EQUIPMENT



Spray down gun & lance.



60m Hose reel with 60m of 3/8" thermoplastic jetting hose & ball valve.




IP68 Professional nozzle kit



Safety whip restraint

## DIMENSIONS (MM)



## TECHNICAL DATA

# TYPHOON HOT 350-23

Product Code	HJ5000-23PHG2-HOT
Pressure / Flow Rate	5075 PSI (350 BAR) / 23 L/PM
Max Water Inlet / Outlet Temp	60°C / 90°C
Class (ASNZS: 4223)	A (8,050 Bar/Litres)
Usage Frequency	Professional - 4 Hours Daily
Nozzle Size	O4
Frame Structure	CNC Modular skid galvanised steel chassis plus satin powder coat finish and <b>stainless steel cover</b>

## MOTOR FEATURES



Engine / Power	Honda™ GX690 Electric Key Start (air cooled) 23 HP / 690 CC
Fuel Type / Capacity / Protection	Unleaded / 17L / Low Oil Shutdown

## HYDRAULIC FEATURES



Pump / Head / Pistons	JW® Italian Triplex Plunger / Brass (Nickle Plated) / Ceramic
Motor Pump Coupling / Pump RPM	Gearbox Drive / 1450RPM
Unloader Valve	Independent (Zero) - Adjustable
Safety Valve	Yes
Detergent Injector	No

## THERMAL FEATURES



Burner Model	Vertical 12v High Flow Series
Fuel Supply / Capacity / Consumption	Diesel / 17L / 5.74 L/PH
Coil / Housing Material	Mild steel 3mm wall seamless (400BAR rated) / Stainless Steel

## DIMENSIONS & WEIGHT



Machine Dimensions / Weight	Skid (no hose reel): 1090mm(L) x 700mm(W) x 920mm(H) / 295KG
-----------------------------	--

## WARRANTY(S)



Unit / Pump Warranty*	 2 Years
Engine Warranty*	 3 Years

## OPTIONAL ACCESSORIES

## OPTIONAL UPGRADES

Remote Mini Reel w/60m 1/4" Hose	PW134-RRCMPL/HOP4	iGX700 EFI Engine Upgrade	ADD:FI
Remote Mini Reel Locking Plate	90012HRH-LP	Van Alloy Drip Tray + Exhaust Mod	JWA432
Forward Root Cutting Nozzle	C43RS	4 Wheel Trolley Kit	JWA407A
15m Viperflex Whip Hose	HOP3VFX15-ASSY	Hose Reel Roller Guide System HGS	1067-GUIDEASSY
Jetting Safety Plate	JSP	Remote Start/Stop	00030
Class B Double Action Foot Valve	55403-DA		

The manufacturer reserves the right to modify design features and technical facts without notice, due to our principals of continuous improvement.  
\*Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).

V2.2 11/21



303 Copland Street, East Wagga Wagga NSW 2650

equipment@amds.com.au

(02) 6921 2011 or 0428 212 011

www.amds.com.au