

GH16000E-FBT/3 16kVA HONDA

**16kVA
HONDA
GH16000E-FBT/3**



ENGINE

MANUFACTURER	Honda
ENGINE MODEL	GX690E
TYPE & CYLINDER	O.H.V.
STARTING	Electric Start
RUN TIME	11hrs @ 60% load
FUEL	Unleaded Petrol
CUBIC CAPACITY	688 cm ³
HP 3000 RPM CONT	14.1HP
OIL CAPACITY	1.9L

TECHNICAL

MODEL	GH16000E-FBT/3
TYPE	Portable
FREQUENCY	50Hz
PHASE/VOLTAGE	3/415

SPEED	POWER		NOISE LEVEL	FUEL CAPACITY	CONTINUOUS OUTPUT
	Max Power		dBA @7m see *1		
	kW	kVA	dBA		
3000RPM	13	16	74	50L	16kVA

ADDITIONAL INFO

OUTLETS	1 x 32 amp 415V 2 x 15 amp 240V switched with thermal overload
FRAME	Skid base with roll frame

ALTERNATOR

ALTERNATOR BRAND	Mecc Alte
TYPE	Brushless
HARMONIC DISTORTION	Less than 5%
INSULATION CLASS	Class H

DIMENSIONS

LENGTH	105cm
WIDTH	77cm
HEIGHT	56cm
WEIGHT	155kg

OPTIONS

- Weather protected IP66 outlets
- 4 wheel kit