

GH16000E-LRT/3

16kVA HONDA

16kVA
HONDA
GH16000E-LRT/3



ENGINE

MANUFACTURER	Honda
ENGINE MODEL	GX690E
TYPE & CYLINDER	O.H.V.
STARTING	Electric Start
RUN TIME	7hrs @ 60% load
FUEL	Unleaded Petrol
CUBIC CAPACITY	688 cm3
HP 3000 RPM CONT	14.1HP
OIL CAPACITY	1.9L

TECHNICAL

MODEL	GH16000E-LRT/3
TYPE	Portable
FREQUENCY	50Hz
PHASE/VOLTAGE	3/415

SPEED	POWER		NOISE LEVEL	FUEL CAPACITY	CONTINUOUS OUTPUT
	Max Power		dBA @7m see *1		
	kW	kVA	dBA		
3000RPM	13	16	74	25L	16kVA

ADDITIONAL INFO

OUTLETS	1 x 32 amp 415V 2 x 15 amp 240V switched with thermal overload
FRAME	Extra large roll frame

ALTERNATOR

ALTERNATOR BRAND	Mecc Alte
TYPE	Brushless
HARMONIC DISTORTION	Less than 5%
INSULATION CLASS	Class H

DIMENSIONS

LENGTH	87cm
WIDTH	70cm
HEIGHT	60cm
WEIGHT	140kg

OPTIONS

- Weather protected IP66 outlets
- RCD/ELCB protection
- 4 wheel kit
- Fuel Tank Base with Roll Over Frame